
Long-term observations of internal waves with shore-based video cameras

Ata Suanda and John A. Barth











What is an internal wave?



Interior oscillations


What is an internal wave?



Alternating currents


Large vertical velocity

The need for monitoring





- Important for mixing and transports
- Understanding the fate of tracers (larvae, nutrients, etc.)
- Internal waves are *intermittent* and affected by *many* oceanographic processes.

Surface expression of IWs




Surface currents create convergences and divergence.






Visible in remote sensing


Internal wave observations are everywhere!



North Pacific Ocean examples



Ramp et al., 2004



Tide-river plume Nash and Moum, 2005 interaction River Plume Mouth 00 N 5 km Canadian Space Agency (2002) 120°W 150°E 150°W 180°W

The difficulty in monitoring

- Satellite pass infrequent
- Rough environment
- Biological growth







Video remote sensing is an alternative...

Single camera view point

Use shore-based video cameras

Pawlowicz, 2003

Propagates onshore ~15 cm/s

Potential for monitoring?



Single camera view point

Use shore-based video cameras

Pawlowicz, 2003


Propagates onshore ~15 cm/s

Potential for monitoring?




Collaborative in-situ + video sensing experiment


Collaborative experiment



Collaborative experiment



Collaborative experiment




Argus system





- Multiple cameras
- Permanent installation ('92 - present)
- Beach processes
- Added offshore camera (2010)






http://cil-www.coas.oregonstate.edu/

Argus system











- Increases field of view
- Camera orientation




Argus system







In-situ measurements



3000

2000

1000

4000


20 and 10-m moorings

• 5 s sampling


Combined picture

15 Aug 2011 (GMT)


10-m temp




Science perspective: 3D views of IWs




Science perspective: Streak propagation






3. Refraction

4. Waves are faster than linear speeds




speeds Properties help differentiate streaks

Potential for monitoring



Many other observed waves


Potential for monitoring



- Many other observed waves
- Cannot see through darkness or fog
- Extend observation period:
 in-situ (4 weeks) ______ camera (14 weeks)



Sea state determines success remote sensing



Toward the use of webcams






- Collaboration with others
- Short in-situ deployments decipher types of waves
- Add data acquisition systems



Toward the use of webcams

...or cloud sourcing!



Summary and future work

- Surface signatures can be used to monitor internal waves from shore-based cameras.
- These signatures can also provide useful information on wave dynamics.
- The success of video remote sensing depends on a number of factors (e.g., visibility, sea state).

- Towards an understanding of inner-shelf waves.
- A statistical description of IW occurrence on the inner shelf.





